AUTHOR INDEX

Abdullayev, A. G., 339
Agrawal, S. L., 157
Armgarth, M., 349

Ballantine, D. S., Jr., 173
Barendsz, A. W., 45
Belford, R. E., 387
Bergs, E. A., 23
Bin, T. Y., 1
Burghartz, J., 91

Conway, P. J., 305

Dabill, D. W., 135
Decoster, D., 239
Dror, M., 23

Eddowes, M. J., 265
Evdokimov, A. V., 339

Fare, T. J., 101
Frindt, R. F., 209

Gabriel, K. J., 189
Gentry, S. J., 135
Gough, D. A., 305
Grate, J. W., 173

Higashi, R. E., 63
Huang, R. S., 1

Jain, K. K., 275
Jenschke, W., 145
Johnson, R. G., 63

Kelly, R. G., 387
Kowalski, G., 367
Krawczyk, S. K., 289

Lundström, I., 349

Miremadi, B. K., 209
Moen, V. A., 209
Molinar, G. F., 275
Moriizumi, T., 309
Morrison, S. Roy, 209, 283
Murshudly, M. N., 339

Nieuwenhuizen, M. S., 45

Otagawa, T., 251
Owen, A. E., 387

Petty-Weeks, S., 377
Polak, A. J., 377

Ramdani, J., 239
Randin, J.-P., 319
Remiens, D., 239
Rhodes, R. K., 23
Robins, I., 73
Rolf, K., 37
Ross, J. F., 73

Salardenne, J., 303
Scheglov, M. I., 339
Schmidt, F. M., 145
Schubert, D., 145
Sears, W. M., 209
Sharma, J. K. N., 275
Smetana, W., 329
Spetz, A., 349
Stetter, J. R., 251
Swami, R., 157

Takatsu, I., 309
Trimmer, W. S. N., 189

Uhlig, T., 145

Verriele, H., 239
von Münch, W., 91

Walsh, P. T., 135
Wang Gui-Hua, 221
Wang Yao-Lin, 221
Webb, B. C., 73
Wiedermann, W., 329
Wohltjen, H., 173

Yu Dun, 221

Zemel, J. N., 101
Ziegler, H., 37
Züllig, F., 319

© Elsevier Sequoia/Printed in The Netherlands

SUBJECT INDEX

Admittance analysis
of PVA/H_3PO_4 proton conducting polymer blends, differential scanning calorimetry and complex, 377
Admittance studies
of hydrogen-induced states at silicon–silicon dioxide interface, 101
Airborne chemicals
chemical concentration modulation sensor for selective detection of, 251
Ammonia-sensitive
metal–oxide–semiconductor structures with Pt gates, optimization of, 349
Ammonia sensitivity
of Pt-gate MOSFET devices; dependence on gate electrode morphology, 73
Arsenic
planar monolithic integrated photoreceiver; association of GaAs Schottky photodiode with GaAs FET, 239

Biosensors
solid state, using thin-film electrodes, 309

CAPSS
thin diaphragm capacitive pressure sensor simulator, 1
Catalytic sensor
for flammable gases, fast-response, 135
Chemical concentration modulation sensor
for selective detection of airborne chemicals, 251
Chemical interface
processes involved at, of SAW chemosensor, 45
Chemical microsensors
automated vapor-generation and data collection instrument for evaluation of, 173
Chemical sensors
introduction to 2nd international meeting on, Bordeaux 1986, 303
Chemosensor
SAW, processes involved at chemical interface of, 45

Dew-point hygrometry
quartz sensor for automatic, 37
Differential scanning calorimetry
and complex admittance analysis of PVA/H_3PO_4 proton conducting polymer blends, 377

Electrodes
potassium ion-selective, based on valinomycin/PVC overlayered solid substrates, 23
solid state biosensors using thin-film, 309
Electrostatic micro-motor
design considerations for a practical, 189
Enzyme electrode-based glucose sensors
long-term *in vitro* operation of, 305

FET
association of GaAs Schottky photodiode with GaAs, planar monolithic integrated photoreceiver, 221

Gallium
planar monlithic integrated photoreceiver; association of GaAs Schottky photodiode with GaAs FET, 239
Gases
flammable, fast-response catalytic sensor for, 135
Gas sensor
based on a transistor structure, 339
platinum hot wire, positive ion emission from 209
Gas sensor operation
mechanism of semiconductor, 283
Gate electrode morphology
ammonia sensitivity of Pt-gate MOSFET devices; dependence on, 73
Glucose sensors
enzyme electrode-based, long-term *in vitro* operation of, 305

Humidity sensors
using integrated capacitive, in thick-film technology, 329

© Elsevier Sequoia/Printed in The Netherlands

Hydrogen-induced states
at silicon–silicon dioxide interface, admittance studies of, 101
Hygrometry
quartz sensor for automatic dew-point, 37

In vitro operation
of enzyme electrode-based glucose sensors, long-term, 305
Ion-selective device
response of enzyme-modified pH-sensitive; analytical solution for response in presence of pH buffer, 265
ISFET
temperature characteristics, 221

Magnetotransistors
with integrated signal amplification, optimization of lateral, 91
Metal–oxide–semiconductor structures
ammonia-sensitive, with Pt gates, optimization of, 349
Micro-motor
electrostatic, design considerations for a practical, 189
Microsensors
chemical, automated vapor-generation and data collection instrument for evaluation of, 173
Microtransducer
for air flow and differential pressure sensing applications, highly sensitive silicon chip, 63
Modulation sensor
chemical concentration, for selective detection of airborne chemicals, 251
MOSFET devices
Pt-gate, ammonia sensitivity of, dependence on gate electrode morphology, 73

Photoreceiver
planar monolithic integrated; association of GaAs Schottky photodiode with GaAs FET, 239
pH-sensitive device
response of enzyme-modified, ion-selective; analytical solution for response in presence of pH buffer, 265
pH sensors
thick-film hybrid, 387
Piezoelectric quartz crystal sensor
relative humidity measurements using, 319
Piezoresistive properties
of polycrystalline and crystalline silicon films, 145
Platinum
ammonia sensitivity of Pt-gate MOSFET devices; dependence on gate electrode morphology, 73
hot wire gas sensor, positive ion emission from, 209
optimization of ammonia-sensitive metal–oxide–semiconductor structures with Pt gates, 349
Polymer blends
PVA/H_3PO_4 proton conducting, differential scanning calorimetry and complex admittance analysis of, 377
Positive ion emission
from platinum hot wire gas sensor, 209
Potassium
K ion-selective electrodes based on valinomycin/PVC overlayered solid substrates, 23
Pressure sensing applications
highly sensitive silicon chip microtransducer for air flow and differential, 63
Pressure sensors
miniature, and their temperature compensation, 367
Pressure sensor simulator
CAPSS, thin diaphragm capacitive, 1
Pressure transducer
use of strain gauge, as working pressure standard up to 500 MPa, 275
PVA/H_3PO_4
proton conducting polymer blends, differential scanning calorimetry and complex admittance analysis of, 377

Quartz crystal sensor
relative humidity measurements using coated piezoelectric, 319
Quartz sensor
for automatic dew-point hygrometry, 37

Relative humidity measurements
using coated piezoelectric quartz crystal sensor, 319

SAW chemosensor
processes involved at chemical interface of, 45
Schottky photodiode
GaAs, association of, with GaAs FET; planar monolithic integrated photoreceiver, 239
Semiconductor gas sensor operation
mechanism of, 283
Senso-opto-micro-electronic devices
SOMET devices, 289
Signal amplification
optimization of lateral magnetotransistors with integrated, 91
Silicon
admittance studies of hydrogen-induced states at silicon–silicon dioxide interface, 101
Silicon chip microtransducer
for air flow and differential pressure sensing applications, highly sensitive, 63
Silicon films
piezoresistive properties of polycrystalline and crystalline, 145
SOMET devices
senso-opto-micro-electronic devices, 289
Strain gauge pressure transducer
use of, as working pressure standard up to 500 MPa, 275
Temperature characteristics
ISFET; 221
Temperature compensation
miniature pressure sensors and their, 367
Thick-film technology
using integrated capacitive humidity sensors in, 329
Transducer
strain gauge pressure, use of, as working pressure standard up to 500 MPa, 275
Transistor
unijunction, dynamic response of, in presence of magnetic field, 157
Transistor structure
gas sensor based on, 339

Unijunction transistor
dynamic response of, in presence of magnetic field, 157

Valinomycin/PVC
overlayered solid substrates, K ion-selective electrodes based on, 23
Vapor-generation
automated, and data collection instrument for evaluation of chemical microsensors, 173